



भारतीय प्रबंध संस्थान कोषिकोड

आई आई एम् कोषिकोड कैम्पस- पी ओ

INDIAN INSTITUTE OF MANAGEMENT KOZHIKODE

IIM Kozhikode Campus P.O., Kozhikode, Kerala - 673 570

No: 11-046/04/WD/NIT-04/Corr-1/2021-IIMK.PUR

12.05.2022

Corrigendum No – 1

Sub: Amendments - Tender for “Procurement of Water Dispensers under buy back”

Ref: Tender No. 11-046/04/WD/NIT-04/2021-IIMK.PUR dt. 04.05.2022.

1. Annexure-I [page 14] of the tender, **Technical Specifications Required for Water Dispenser**, is revised and attached as **Annexure-I (Revised)**.
2. All other terms & conditions of the tender documents remain unchanged. The Corrigendum notice is also available at IIMK website <https://iimk.ac.in/tender> as well as <https://mhrd.euniwizarde.com>.

Sd/-
Chief Purchase Officer

Annexure-I (Revised)

Technical Specifications Required for Water Dispenser (with Hot, Cold & Normal Water Faucets)

SI No	Specifications	Range	
1.	Approximate Size:		
	a) Width	350 – 400 mm.	
	b) Depth	300 – 400 mm.	
	c) Height	1000 - 1500 mm.	
2.	Options	Normal, Hot & Cool	
3.	Flow rate	Not less than 50 Litres/Hour	
4.	Storage Tank :	Capacity	Discharge
	(a) Normal Water	08-10 Litres	10-35 Litres/Hour
	(b) Cold Water	03-07 Litres	10-35 Litres/Hour
	(c) Hot Water	01-05 Litres	2-10 Litres/Hour
5.	Purification	UV Purifier (or high end/state-of-the art technology)	
6.	Temperature		
	(a) Heater	50-85 ^o C (Stainless steel heater Coil)	
	(b) Cooler	10-23 ^o C	
7.	Weight (without water)	30- 60 kg	
8.	Power Supply	180-260 Volts	
9.	No. of water faucets	1 No. each (CP Brass/ABS Material) for Cold, Hot & Normal Water	
10.	Compressor Refrigerant	R 22 or R 134A or approved equivalent	
11.	Condenser Fan	Propeller Type(Quiet)/ Grooved copper or approved equivalent	
12.	Thermostat	Automatically controls temperature	
13.	Water Connection:	Inlet	Drain
		High quality and food graded piping system with Stainless steel	High quality and food graded piping system with Stainless steel/ABS Material drip tray
14.	Housing/Body	Stainless steel not less than 0.80 mm thick with minimum SS304	
15.	Legs	Stainless steel not less than 2.00 mm thick with minimum SS304	
16.	Tanks		
	(a) Hot Water	Stainless steel not less than 0.80 mm. thick with minimum SS304	
	(b) Cold Water		
	(c) Normal Water		
17.	Warranty	Not Less than 24 Months and Extended All Inclusive Comprehensive AMC for Thirty Six Months	
18.	Stabilizer	Inbuilt with required VA or External Stabilizer V-Guard 1000 VA	
19.	Preferable brands	Voltas / Blue Star /Aguaclan/ Cross Fields /Eureka Forbes	